

CORUS MC1-H946



Dimensions	– 430 (W) x 252 (D) x 44 (H) mm
Form	Mini ITX (6.7-in * 6.7-in, 170 * 170mm)
CPU - Chipset	– Intel® 8/9th Core Processor TDP max 65 W (35W conseillé) – Intel C246 Express
Memoires	– 2* Dual CH non-ECC DDR4 2400/2666 MHz SDRAM SO-DIMM up to 64GB
Video - Audio	– Intel HD Graphics selon le CPU – Gestion 3 écrans max – Résolution max HDMI : 4096x2160@30Hz – Résolution max DP : 4096x2304@60Hz – Résolution max VGA : 1920x1080@60Hz – 6 channel HD Audio Relatek ALC888S
LAN	– 1*Intel i219LM GbE + 1* Intel i225LM 2.5 GbE
Storage	– Contrôleur SATA3 6Gb/s avec support RAID 0, 1, 5 – Support 1 disk 3.5 ou 1 à 3 disks 2.5 – 1 *M.2_SSD (M key-2242/2280) support NVMe
Extensions	– 1* M.2 E-key 2230 (PCIex1/USB2.0) support CNVi – Option Support onboard TPM2.0 (MI98-02) – 1 * Slot AR (Riser card optionnel) – 1 PCIe x16
Connecteurs AR	– 4 * USB 3.1 (Gen. 2) + 2 USB 3.1 (Gen 1) – 3 video (HDMI, DP, VGA)– 2 * RJ45 (1*Intel i219LM, 1* Intel i225LM) – 1 * Mic , 1 * Line in , 1 * Line-out – AC in – 2 * COM (support RS232/422/485)
Panel avant	– Power button - Reset button - Power LED - HDD LED - 2 * USB 2.0
Watchdog Timer	– 256 segments (10s – 255 mn)
Alimentation Système Fan	– 1U 200W FLEX POWER - AC 90~240V input – 3 * FAN 40x20 7000 RPM DC 12v 0.1A
Environnement Certification	– Operating Temperature : 0°C~50°C - Storage Temperature : -10°C~70°C – Humidity: 10% ~ 90% RH @40°C (non-condensing) – CE, FCC, LVD, RoHS
Packing	– Net Weight : 4.5 KG - Gross Weight : 5.5 KG – Packing Box Dimension : 560(W) x 400(D) x 140(H) mm
OS support	– Windows 10, Windows Server 2019, Linux
Garantie	1 An Standard retour atelier (RA)